C930

14A504

A143
Overhead console



F12056

Pin	Circuit	Circuit function
1	294 (WH/LB)	Voltage in Run (overload protected)
2	875 (BK/LB)	Ground
3	679 (GY/BK)	Vehicle Speed Sensor (VSS) +
4	19 (LB/RD)	Instrument illumination, feed
5	767 (LB/OG)	Ambient air temperature sensor (19E702), feed
6	470 (PK/BK)	Sensor signal return (reference/ground)
7	53 (BK/LB)	Interior lamp relay, switched power, output
8	705 (LG/OG)	Battery saver relay, switched power
9	57 (BK)	Ground
10	1173 (BN/OG)	Roof opening panel switch (15B691), common
11	1174 (WH/RD)	Roof opening panel switch (15B691), Open, signal
12	1175 (TN/RD)	Roof opening panel switch (15B691), closed, signal

C941

14A504

E246
Rail lamp, LH side
(13776)



F03173

Pin	Circuit	Circuit function
1	705 (LG/OG)	Battery saver relay, switched power
2	57 (BK)	Ground
3	53 (BK/LB)	Interior lamp relay, switched power, output

C942

14A504

E245
Rail lamp, RH side
(13776)



F03072

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	53 (BK/LB)	Interior lamp relay, switched power, output
3	705 (LG/OG)	Battery saver relay, switched power

C958

13A625

E227
Cargo lamp 2



F02237

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	53 (BK/LB)	Interior lamp relay, switched power, output