## C291 (GY)

**14401**




F08333

**13A718**




F08339

(1) 2 (WH/LB)
(2) 3 (LG/WH)
(3) 14 (BN)
(4) 37 (YE)
(5) –
(6) 49 (OG)
(7) 511 (LG)
(8) 19 (LB/RD)

## C294a (RD)

**14401**

Function selector switch assembly, front




F04027

| Pin | Circuit | Circuit function |
|---|---|---|
| 1 | 489 (PK/BK) | Voltage in Run (overload protected) |
| 2 | 753 (YE/RD) | Function selector switch assembly, front, output |
| 3 | 348 (VT) | A/C demand signal |
| 4 | 489 (PK/BK) | Voltage in Run (overload protected) |

## C294b (BK)

**14401**

Function selector switch assembly, front




F04193

| Pin | Circuit | Circuit function |
|---|---|---|
| 1 | 261 (OG/BK) | Front blower motor (19805), output |
| 2 | 57 (BK) | Ground |
| 3 | 260 (RD/OG) | medium low |
| 4 | 269 (LB/OG) | medium high |

## C294c (GY)

**14401**

Function selector switch assembly, front




F06349

| Pin | Circuit | Circuit function |
|---|---|---|
| 1 | 752 (YE/RD) | medium low |
| 2 | 757 (RD/WH) | Rear A/C blower speed relay 2, control |
| 3 | – | not used |
| 4 | 57 (BK) | Ground |
| 5 | 751 (DB/WH) | medium high |
| 6 | 754 (LG/WH) | Low |