C168

15525

A440
4R70W transmission



F10076

Pin	Circuit	Circuit function
1	–	not used
2	359 (GY/RD)	Signal return
3	480 (VT/YE)	Torque Converter Clutch (TCC) solenoid
4	1138 (VT/WH)	Voltage supplied in Start and Run (overload protected)
5	923 (OG/BK)	Transmission Fluid Temperature (TFT) sensor, input
6	925 (WH/YE)	Electronic Pressure Control (EPC) solenoid
7	237 (OG/YE)	Shift solenoid A
8	315 (VT/OG)	Shift solenoid B
9	–	not used
10	–	not used

C169

15525

N19
Reversing lamps switch



F02471

Pin	Circuit	Circuit function
1	140 (BK/PK)	Voltage supplied in reverse, output
2	295 (LB/PK)	Voltage in Run (overload protected)

C171

12B637/15525/9D930

B48
Heated Oxygen Sensor (HO2S) #11 (9F472)



F04075

Pin	Circuit	Circuit function
1	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
2	387 (RD/WH)	Heated Oxygen Sensor (HO2S) #11 (9F472), heater
3	359 (GY/RD)	signal, return
4	74 (GY/LB)	signal

C172

12B637/15525/9D930

B47
Heated Oxygen Sensor (HO2S) #21 (9F472)



F04075

Pin	Circuit	Circuit function
1	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
2	388 (YE/LB)	Heated Oxygen Sensor (HO2S) #21 (9F472), heater
3	359 (GY/RD)	signal, return
4	94 (RD/BK)	signal

C174

12B637/9D930

U10
Ignition transformer capacitor 1 (18801)

F01079

Pin	Circuit	Circuit function
1	16 (RD/LG)	Voltage supplied in Start and Run (overload protected)