C228a

14401

Electronic Automatic Temperature Control (EATC) module (19980)



F13013

Pin	Circuit	Circuit function
1	915 (PK/LB)	SCP Bus –
2	54 (LG/YE)	Voltage supplied at all times (overload protected)
3	676 (PK/OG)	Ground
4	470 (PK/BK)	Sensor signal return (reference/ground)
5	–	not used
6	436 (RD/LG)	Air temperature door variable resistor +
7	767 (LB/OG)	Ambient air temperature sensor (19E702), feed
15	914 (TN/OG)	SCP Bus +
16	298 VT/OG	Voltage in Run (overload protected)
17	–	not used
18	437 (YE/LG)	Air temperature door variable resistor, wiper
19	19 (LB/RD)	Instrument illumination, feed
20	476 (BN/YE)	Sunload sensor (19E663), input

C228b

14401

Electronic Automatic Temperature Control (EATC) module (19980)



F13015

Pin	Circuit	Circuit function
8	1070 (BN/LB)	Remote control unit, control
9	438 (RD/WH)	Air temperature door variable resistor –
10	269 (LB/OG)	blower motor, control, input
11	348 (VT)	A/C demand signal
12	–	not used
13	245 (BN/LG)	Temperature blend door actuator (19E616), control
14	484 (OG/BK)	Interior lamps, feed
21	790 (WH/OG)	In–vehicle temperature sensor (19C734), input
22	–	not used
23	752 (YE/RD)	blower motor, except Duratec–VE engines, output
24	754 (LG/WH)	blower motor, High
25	506 (RD)	Message center switch, output
26	246 (VT)	Temperature blend door actuator (19E616), control

C233

14401

In–vehicle temperature sensor (19C734)



F02493

Pin	Circuit	Circuit function
1	790 (WH/OG)	In–vehicle temperature sensor (19C734), input
2	470 (PK/BK)	Sensor signal return (reference/ground)