C1008

12A581

A/C clutch relay



F05129

Pin	Circuit	Circuit function
85	331 (PK/YE)	A/C clutch relay, control
86	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
30	326 (WH/VT)	Voltage supplied at all times (overload protected)
87A	–	not used
87	321 (GY/WH)	A/C clutch relay, switched output

C1010

* 6.0L Diesel
** all others

15525



F16087

(1) *16 (RD/LG)
**359 (GY/RD)
(2) *511 (LG)
**970 (DG/WH)
(3) *463 (RD/WH)
**136 (DB/YE)
(4) 923 (OG/BK)
(5) 924 (BN/OG)
(6) *359 (GY/RD)
**480 (VT/YE)
(7) *64 (DG)
**237 (OG/YE)
(8) *52 (YE)
**315 (VT/OG)

12A581



F16020

(9) 925 (WH/YE)
(10) *324 (YE/LG)
**391 (RD/YE)
(11) *911 (WH/LG)
**199 (LB/YE)
(12) *5 (OG/LB)
**33 (WH/PK)
(13) *9 (LG/OG)
**1093 (TN/RD)
(14) *787 (PK/BK)
**1144 (YE/BK)
(15) *519 (LG/BK)
**1145 (LB/BK)
(16) *523 (RD/PK)
**1143 (WH/BK)