C169

12B637

N19
Reversing lamps
switch



Pin	Circuit	Circuit Function
1	140 (BK/PK)	Voltage supplied in reverse
2	298 (VT/OG)	Voltage in Run (overload protected)

C171

12B637

B48
Heated Oxygen
Sensor (HO2S) #11



F04082

Pin	Circuit	Circuit Function
1	34 (LB/OG)	Voltage supplied in Start and Run (overload protected)
2	387 (RD/WH)	Heated Oxygen Sensor (HO2S) #11, heater
3	89 (OG)	signal, return
4	74 (GY/LB)	Heated Oxygen Sensor (HO2S) #11, input

C172 (BU)

12A690 Before Jan 31

12B637 As of Jan 31

B47
Heated Oxygen
Sensor (HO2S) #21



F04082

Pin	Circuit	Circuit Function
1	34 (LB/OG)	Voltage supplied in Start and Run (overload protected)
2	388 (YE/LB)	Heated Oxygen Sensor (HO2S) #21, heater
3	89 (OG)	signal, return
4	94 (RD/BK)	Heated Oxygen Sensor (HO2S) #21, input

C174 (GY)

12B637

U10
Ignition transformer
capacitor 1

F01031

Pin	Circuit	Circuit Function
1	16 (RD/LG)	Voltage supplied in Start and Run (overload protected)