C205b

14401

N113
Main light switch
(11654)



F12075

Pin	Circuit	Circuit function
1	–	not used
2	188 (WH/BK)	Hot with Headlamps on
3	–	not used
4	–	not used
5	275 (YE)	Fog lamp relay, control
6	57 (BK)	Ground
7	1525 (LG/RD)	Main light switch (11654), switched power
8	196 (DB/OG)	Voltage supplied at all times (overload protected)
9	15 (RD/YE)	Power, Hot with Headlamps on
10	195 (TN/WH)	Voltage supplied at all times (overload protected)
11	257 (WH/RD)	Hot in Park or Head
12	14 (BN)	Power, Exterior lamps

C210

14401



F04140

14A504



F04138

(1) 556 (DG)
(2) 1153 (RD/BK)
(3) 57 (BK)
(4) 400 (LB/BK)

*Supercrew

C211

14401



F16089

14A504



F16087

(1) 1543 (YE)
*802 (OG/RD)
(2) 470 (PK/BK)
(3) 140 (BK/PK)
(4) 53 (BK/LB)
(5) 767 (LB/OG)
(6) 803 (BN/PK)
(7) –
(8) 705 (LG/OG)
(9) 800 (GY/LB)
*404 (VT/LG)
(10) 679 (GY/BK)
(11) 294 (WH/LB)
(12) 511 (LG)
(13) 801 (TN/YE)
*405 (VT/LB)
(14) 19 (LB/RD)
(15) 875 (BK/LB)
(16) 85 (BN/LB)