C1195

14290

P133
Vapor management valve



F02105

Pin	Circuit	Circuit Function
1	34 (LB/OG)	Voltage supplied in Start and Run (overload protected)
2	191 (LG/BK)	Powertrain Control Module (PCM), Vapor management valve

C1197

14290

K359
Medium speed fan control relay



F05107

Pin	Circuit	Circuit Function
30	3829 (LB/BK)	Medium speed fan control relay, output
85	3886 (DB/GY)	Medium speed fan control relay, control
86	296 (WH/VT)	Voltage supplied in Start and Run (overload protected)
87	60 (BK/LG)	Voltage supplied at all times (overload protected)
87A	-	not used

C2007

14401

A271
Passive anti–theft transceiver



F04245

Pin	Circuit	Circuit Function
1	296 (WH/VT)	Voltage supplied in Start and Run (overload protected)
2	57 (BK)	Ground
3	167 (BN/OG)	TX, signal
4	168 (RD/BK)	RX, signal

C2008

14401

Y215
Brake shift interlock



F08179

Pin	Circuit	Circuit Function
1	665 (OG/YE)	Overdrive cancel switch, signal
2	570 (BK/WH)	Ground
3	57 (BK)	Ground
4	640 (RD/YE)	Voltage supplied in Start and Run (overload protected)
5	605 (RD)	Voltage supplied at all times (not overload protected)
6	-	not used
7	1415 (LB/YE)	Switched, Ground
8	1420 (YE/LB)	Key removal inhibit solenoid, Switched, Ground