C3198a (GY)

14B079

Auxiliary function selector switch assembly, rear



F06229

Pin	Circuit	Circuit function
1	756 (RD/PK)	Auxiliary blower motor (19805), Low
2	269 (LB/OG)	Auxiliary blower motor (19805), medium low
3	–	not used
4	751 (DB/WH)	Auxiliary blower motor (19805), medium high
5	515 (OG/RD)	Auxiliary blower motor (19805), speed control
6	1120 (BK/WH)	Auxiliary function selector switch assembly, rear, Enable

C3198b (WH)

* Navigator

14B079

Auxiliary function selector switch assembly, rear



F10125

Pin	Circuit	Circuit function
1	–	not used
2	1129 (BN/WH)	return, from, Auxiliary function selector switch assembly, rear
3	1130 (PK/LG)	auxiliary mode door, signal, from, Auxiliary function selector switch assembly, rear
4	1128 (GY/LB)	feed to Auxiliary function selector switch assembly, rear
5	–	not used
6	19 (LB/RD)	Illumination, Power
	*1417 (LG/RD)	Light emitting diode (LED), Illumination
7	–	not used
8	–	not used
9	57 (BK)	Ground
10	243 (LG/OG)	auxiliary blend door, signal, from, Auxiliary function selector switch assembly, rear