C295

19D887

Cool air bypass actuator (19E616)



F06179

Pin	Circuit	Circuit function
1	32-FB2 (WH/RD)	Switched between: Battery voltage, Ground or Open
2	–	not used
3	8-FB2 (WH/RD)	Sensor signal
4	9-FB2 (BN/RD)	Sensor signal return (reference/ground)
5	7-FB2 (YE/RD)	Voltage DC supplied at all times (sensor)
6	33-FB2 (YE/RD)	Switched between: Battery voltage, Ground or Open

C296

19D887

Evaporator discharge air temperature sensor (19C734)



F02047

Pin	Circuit	Circuit function
1	9-FA44 (BN/RD)	Sensor signal return (reference/ground)
2	8-FA44 (WH/RD)	Sensor signal

C297 (GY)

19D887

Heater blower control module



F04347

Pin	Circuit	Circuit function
1	31S-FA18 (BK/RD)	Heater blower motor (19805), control
2	31-FA45 (BK/OG)	Ground
3	8-FA45 (WH/BU)	Blower motor, control, signal
4	30S-FA45 (RD/OG)	Blower motor relay, switched power, output

C300 (GY)

14A005



F04140

(1) 31-AH14 (BK)
(2) –
(3) 30-AH14 (RD/YE)
(4) –

14A699



F04138

(1) 31-AH14 (BK)
(2) –
(3) 30-AH14 (RD)
(4) –