C282 (GY)

14401

N316
Inertia Fuel Shutoff
(IFS) switch
(9D362)



F03130

Excursion

Pin	Circuit	Circuit function
1	238 (DG/YE)	Fuel pump relay, switched power, output
2	–	not used
3	787 (PK/BK)	Fuel pump, Power

C284

14401

N141
Four–wheel drive
switch



F04027

Pin	Circuit	Circuit function
1	19 (LB/RD)	Illumination +
2	780 (DB)	Four–wheel drive control module, to, Four–wheel drive switch
3	465 (WH/LB)	Four–wheel drive control module, to, Four–wheel drive switch
4	57 (BK)	Ground

C286

14401

B72
Sunload sensor
(19E663)



F03197

Pin	Circuit	Circuit function
1	217 (DB/OG)	signal to Electronic Automatic Temperature Control (EATC) module (19980)
2	57 (BK)	Ground
	676 (PK/OG)	Ground
3	1104 (LB)	signal to Vehicle Security Module (VSM)

C289

14401

M256
Temperature blend
door actuator
(19E616)



F08059

Pin	Circuit	Circuit function
1	437 (YE/LG)	Air temperature door variable resistor, wiper, with EATC
	–	not used, manual A/C
2	–	not used
3	437 (YE/LG)	Air temperature door variable resistor, wiper, manual A/C
	–	not used, with EATC
4	436 (RD/LG)	Air temperature door variable resistor –, manual A/C
	–	not used, with EATC
5	436 (RD/LG)	Air temperature door variable resistor, –, with EATC
	–	not used, manual A/C
6	438 (RD/WH)	Air temperature door variable resistor, +
7	249 (DB/LG)	Blend door actuator, CW, with EATC
	296 (WH/VT)	Voltage, hot in run only, manual A/C
8	250 (OG)	Blend door actuator, CCW, with EATC
	57 (BK)	Ground, manual A/C