C2159 (GY)

14A005

Adjustable pedal motor (2C429)



F06112

Pin	Circuit	Circuit function
1	447 (OG/RD)	Signal return
2	1491 (LB/YE)	Adjustable pedal motor (2C429), position sense
3	446 (OG/WH)	Reference voltage
4	–	not used
5	1489 (LB/BK)	motor drive +/–
6	1490 (LB/OG)	motor drive +/–

C2214

14290

SSP 3 relay



F05051

Pin	Circuit	Circuit function
30	1447 (RD)	Voltage supplied at all times (overload protected)
85	1447 (RD)	Voltage supplied at all times (overload protected)
86	1330 (YE/LB)	Coil, Switched ground
87	1455 (GY/RD)	switched power
87A	–	not used

C2215

SSP 4 relay



F05051

Pin	Circuit	Circuit function
30	1448 (OG/RD)	Voltage supplied at all times (overload protected)
85	1448 (OG/RD)	Voltage supplied at all times (overload protected)
86	1330 (YE/LB)	Coil, Switched ground
87		switched power
87A	–	not used

C2216

Front blower motor relay



F05051

Pin	Circuit	Circuit function
30	364 (BK/LG)	Voltage supplied at all times (overload protected)
85	364 (BK/LG)	Voltage supplied at all times (overload protected)
86	1322 (BN/WH)	Coil, Switched ground
87	371 (PK/WH)	Blower motor, relay control battery feed
87A	–	not used

C2217

Auxiliary blower motor relay



F05051

Pin	Circuit	Circuit function
30	181 (BN/OG)	Voltage supplied at all times (overload protected)
85	181 (BN/OG)	Voltage supplied at all times (overload protected)
86	1371 (TN/OG)	Coil, Switched ground
87	536 (BK/LG)	Blower motor, relay control battery feed
87A	–	not used