C1198 (BK)

12A581

Air suspension solid state relay (2C013)

Early production



F04079

Pin	Circuit	Circuit function
A	1053 (LB/PK)	Voltage supplied at all times (overload protected)
B	538 (GY/RD)	Air suspension solid state relay (2C013), output
C	577 (LG/RD)	Air pump motor, Ground
D	420 (DB/YE)	Air suspension solid state relay (2C013), control

C1209 (BK)

12A581

IVD stop lamp relay



F05110

Pin	Circuit	Circuit function
1	10 (LG/RD)	Voltage supplied at all times (overload protected)
2	1787 (RD/LG)	IVD stop lamp relay, control
3	10 (LG/RD)	Voltage supplied at all times (overload protected)
4	–	not used
5	511 (LG)	Brake pedal position switch (13480), to stoplamps

C1274 (WH)

15525

4R70W transmission



F10093

Pin	Circuit	Circuit function
1	1138 (VT/WH)	Voltage supplied in Start and Run (overload protected)
2	480 (VT/YE)	Torque Converter Clutch (TCC) solenoid
3	359 (GY/RD)	signal, return
4	–	not used
5	315 (VT/OG)	Shift solenoid B
6	237 (OG/YE)	Shift solenoid A
7	925 (WH/YE)	Electronic Pressure Control (EPC) solenoid, control
8	923 (OG/BK)	Transmission Fluid Temperature (TFT) sensor, input
9	–	not used
10	–	not used

C1300

12A581

Air suspension compressor relay



F04429

Pin	Circuit	Circuit function
1	883 (PK/LB)	Voltage supplied at all times (overload protected)
2	420 (DB/YE)	Air suspension compressor relay, control
3	1053 (LB/PK)	Voltage supplied at all times (overload protected)
5	538 (GY/RD)	Air suspension compressor relay, output