R4.65

14398

HID headlamp relay, left



Pin	Circuit	Circuit Function
1	13 (RD/BK)	Voltage supplied with headlamps on
2	1205 (BK)	Coil ground
3	1338 (WH)	Voltage supplied at all times (overload protected)
4	–	not used
5	160 (DB/WH)	Relay switched output to left low beam

R4.66

14398

Engine cooling fan relay



Pin	Circuit	Circuit Function
85	1154 (WH/BK)	Aux. condenser cooling fan relay control feed
86	1153 (RD/BK)	Aux. condenser cooling fan relay, B+ feed
87	1155 (YE/BK)	Aux. condenser cooling fan feed
87A	–	not used
30	1153 (RD/BK)	Aux. condenser cooling fan relay, B+ feed

R5.1

19D887

Auxiliary A/C relay



Pin	Circuit	Circuit Function
85	1205 (BK)	Coil ground
86	575 (YE/BK)	Voltage supplied to coil in run/start (overload protected)
87	371 (PK/WH)	Blower motor relay, switched output
87A	–	not used
30	181 (BN/OG)	Voltage supplied at all times (overload protected)

D1.60

14398

Powertrain Control Module (PCM) diode



Pin	Circuit	Circuit Function
1	20 (WH/LB)	Voltage supplied in start and run (overload protected)
2	845 (TN/BK)	Voltage supplied at all times (overload protected)

D1.61

14398

A/C indicator clutch diode



Pin	Circuit	Circuit Function
1	1205 (BK)	Ground
2	321 (GY/WH)	A/C clutch relay, switched output

CB1.62

14398

Accessory delay circuit breaker (30 amp)



Pin	Circuit	Circuit Function
1	645 (WH/LB)	Voltage supplied at all times (overload protected)
2	645 (WH/LB)	Voltage supplied at all times (overload protected)