C169

12B637

N19
Reversing lamps
switch

4.0L, 2.3L



F02353

3.0L



F02355

Pin	Circuit	Circuit function
1	140 (BK/PK)	Voltage supplied in reverse
2	298 (VT/OG)	Voltage in Run (overload protected)

C171 (GY)

12B637

B48
Heated Oxygen
Sensor (HO2S) #11
(9F472)



F04075

Pin	Circuit	Circuit function
1	34 (LB/OG)	Voltage supplied in Start and Run (overload protected)
2	387 (RD/WH)	Heated Oxygen Sensor (HO2S) #11 (9F472), heater
3	89 (OG)	signal, return
4	74 (GY/LB)	Heated Oxygen Sensor (HO2S) #11 (9F472), input

C172 (GY)

12B637

B47
Heated Oxygen
Sensor (HO2S) #21
(9F472)



F04075

Pin	Circuit	Circuit function
1	34 (LB/OG)	Voltage supplied in Start and Run (overload protected)
2	388 (YE/LB)	Heated Oxygen Sensor (HO2S) #21 (9F472), heater
3	89 (OG)	signal, return
4	94 (RD/BK)	Heated Oxygen Sensor (HO2S) #21 (9F472), input

C174

12B637

U10
Ignition transformer
capacitor 1 (18801)



F01031

Pin	Circuit	Circuit function
1	16 (RD/LG)	Voltage supplied in Start and Run (overload protected)