PIN	CIRCUIT	CIRCUIT FUNCTION
91	359 (GY/RD)	Signal Return
92	810 (RD/LG)	Brake Pedal Position (BPP) Switch Input
93	387 (RD/WH)	Heated Oxygen Sensor #11 (HO2S) Heater
94	388 (YE/LB)	Heated Oxygen Sensor #21 (HO2S) Heater
95	389 (WH/BK)	Heated Oxygen Sensor #12 (HO2S) Heater (Catalyst Monitor)
96	–	NOT USED
97	361 (RD)	Power (PWR)
98	–	NOT USED
99	560 (LG/OG)	Fuel Injector #6 Control
100	558 (BN/LB)	Fuel Injector #4 Control
101	556 (WH)	Fuel Injector #2 Control
102	–	NOT USED
103	570 (BK/WH)	Power Ground
104	–	NOT USED



C311
FUEL TANK ASSEMBLY
(HARNESS SIDE)

PIN	CIRCUIT	CIRCUIT FUNCTION
1	351 (BN/WH)	Reference Voltage
2	640 (RD/YE)	Power (Hot in Start or Run)
3	787 (PK/BK)	Fuel Pump Power
4	396 (BK/OG)	Dedicated Ground
5	791 (RD/PK)	Sensor Signal Return
6	359 (GY/RD)	Fuel Tank Pressure Sensor to PCM
7	57 (BK)	Ground
8	29 (YE/WH)	Fuel Gauge to Fuel Gauge Sender