C350 (BK)

14A005

Transfer case assembly



F08259

Pin	Circuit	Circuit function
1	770 (WH)	Motor position B
2	764 (BN/WH)	Motor position C
3	763 (OG/WH)	Motor position D
4	777 (YE)	Transfer case, Low to High, feed
5	771 (VT/YE)	Motor position A
6	762 (YE/WH)	Motor position, return
7	778 (OG)	Transfer case, High to Low, feed
8	779 (BN)	Differential lock solenoid, control

* with memory

C352 (BK)

14A699

Power seat switch, left



F08273

Pin	Circuit	Circuit function
1	57 (BK)	Ground
	*875 (BK/LB)	Ground
2	978 (YE/LB)	Driver seat front height motor, Up, feed
	*1463 (RD/YE)	Driver seat front height motor, Up, signal
3	981 (RD/WH)	Driver seat horizontal motor, Rearward, feed
	*1466 (GY/OG)	Driver seat rear height motor, Rearward, signal
4	983 (RD/LG)	Driver seat rear height motor, Down, feed
	*1467 (GY/YE)	Driver seat rear height motor, Down, signal
5	980 (YE/WH)	Driver seat horizontal motor, Forward, feed
	*1465 (GY/WH)	Driver seat horizontal motor, Forward, signal
6	982 (YE/LG)	Driver seat rear height motor, Up, feed
	*1468 (GY/LB)	Driver seat rear height motor, Up, signal
7	566 (DG)	Voltage supplied at all times (overload protected)
	*956 (OG/LG)	Voltage supplied at all times (overload protected)
8	979 (RD/LB)	Driver seat front height motor, Down, feed
	*1464 (YE)	Driver seat front height motor, Down, signal