C1008

14398

A/C clutch relay



F05110

Pin	Circuit	Circuit function
1	1139 (VT/YE)	Voltage supplied in Start and Run (overload protected)
2	331 (PK/YE)	A/C clutch relay, control
3	1003 (GY/YE)	Voltage supplied in Start and Run (overload protected)
4	–	not used
5	321 (GY/WH)	A/C clutch relay, switched output

C1016

14398

PCM power relay



F05051

Pin	Circuit	Circuit function
87	361 (RD)	PCM power relay, switched output
87A	–	not used
86	845 (TN/BK)	Voltage supplied in Start and Run (overload protected)
85	1205 (BK)	Ground
30	1075 (BN/LB)	Voltage supplied at all times (overload protected)

C1011

14398

Blower motor relay



F05051

Pin	Circuit	Circuit function
87	371 (PK/WH)	Blower motor relay, switched output
87A	–	not used
86	1205 (BK)	Ground
85	575 (YE/BK)	Blower motor relay, control
30	538 (GY/RD)	High speed cooling fan relay, switched power

C1017

14398

Starter relay (11450)



F05051

Pin	Circuit	Circuit function
87	113 (YE/LB)	Starter motor (11002) to Starter relay (11450)
87A	–	not used
86	461 (OG)	PCM, to starter motor relay
85	33 (WH/PK)	switched power, to Starter relay (11450)
30	1050 (LG/VT)	Voltage supplied at all times (overload protected)