C2248

14401

Panel/Defrost
mode actuator



F06128

Pin	Circuit	Circuit function
1	1379 (PK/LB)	Blend door actuator, signal
2	–	not used
3	1123 (YE/WH)	Air temperature door variable resistor, wiper
4	438 (RD/WH)	Air temperature door variable resistor –
5	436 (RD/LG)	Air temperature door variable resistor +
6	1380 (TN/YE)	Blend door actuator, control

C2253a (GY)

14401

Audio/naviga-
tion control unit



F24021

Pin	Circuit	Circuit function
1	828 (VT/LB)	Voltage supplied at all times (overload protected)
2	1523 (DG)	Fused accessory relay, switched power, output
3	484 (OG/BK)	Instrument illumination, on input
4	57 (BK)	Ground
5	–	not used
6	–	not used
7	723 (GY/RD)	not used
8	–	not used
9	–	not used
10	–	not used
11	–	not used
12	–	not used
13	694 (BK/LG)	Ground
14	–	not used
15	689 (DB)	Voltage supplied in Start (overload protected)
16	–	not used
17	–	not used
18	595 (LB/RD)	Auxiliary audio controls, steering wheel, Reference voltage
19	–	not used
20	1442 (DG/WH)	not used
21	–	not used
22	–	not used
23	–	not used
24	694 (BK/LG)	Ground