C316 (BK)

14C719



F12155

(1) 566 (DG)
(2) –
(3) 979 (RD/LB)
(4) 981 (RD/WH)
(5) 983 (RD/LG)
(6) 566 (DG)

14B084



F12153

(7) –
(8) –
(9) 990 (YE/LB)
(10) 980 (YE/WH)
(11) 982 (YE/LG)
(12) 1205 (BK)

C360

14B084

Seat adjust switch, driver side front (14A701)



F08245

Pin	Circuit	Circuit function
1	983 (RD/LG)	Rear height motor, Up +/–
2	566 (DG)	Voltage supplied at all times (overload protected)
3	981 (RD/WH)	Fwd/Rwd motor, Forward
4	1205 (BK)	Ground
5	990 (YE/LB)	Front height motor, Down
6	982 (YE/LG)	Rear height motor, Down +/–
7	979 (RD/LB)	Front height motor, Up
8	980 (YE/WH)	Fwd/Rwd motor, Rearward

C323 (GY)

* without power seats, without power lumbar

***14A546**
14C719

Safety belt buckle switch (10B924)



F02088

Pin	Circuit	Circuit function
1	85 (BN/LB)	Safety belt buckle switch (10B924), input
2	1205 (BK)	Ground

C361

* without power seats, with power lumbar
** Cobra, with power seats, with power lumbar

14B084
***14C719**

Lumbar adjust switch, left front (14B691)



F02088

Pin	Circuit	Circuit function
1	566 (DG)	Voltage supplied at all times (overload protected)
2	*51 (BK/WH)	Lumbar adjust switch, left front (14B691), output
	**1205 (BK)	Ground