C270b

* with High Intensity Discharge (HID) lamps

14290

Central Junction Box (CJB) (14A068)



F10042

Pin	Circuit	Circuit function
1	15-RD6 (GN/OG)	Voltage supplied in Start and Run (overload protected)
2	29S-LF3 (OG/YE)	fused feed, Switched System Power (SSP) 1
3	50-BB15 (GY/OG)	Voltage supplied in Start (overload protected)
4	29S-LE23 (OG/WH)	fused feed, Switched System Power (SSP) 1
	*29S-LE2 (OG/BU)	fused feed, Switched System Power (SSP) 1
5	29S-LE16 (OG/GN)	fused feed, Switched System Power (SSP) 2
	*29S-LE1 (OG/YE)	fused feed, Switched System Power (SSP) 2
6	29S-LF4 (OG/BU)	fused feed, Switched System Power (SSP) 1
7	–	Voltage supplied in Start and Run (overload protected)
8	29S-LE22 (OG/GN)	fused feed, Switched System Power (SSP) 2
9	–	not used
10	29S-LE15 (OG/BK)	fused feed, Switched System Power (SSP) 1

C270c

14290

Central Junction Box (CJB) (14A068)



F06199

Pin	Circuit	Circuit function
1	–	not used
2	29-DK1 (OG/YE)	Voltage supplied at all times (overload protected)
3	29S-DK21 (OG/WH)	fused feed, Switched System Power (SSP) 2
4	20-CF6 (PK/YE)	Voltage in Run (overload protected)
5	29-RE8 (OG/YE)	Voltage supplied at all times (overload protected)
6	–	not used