90-5 TURN/STOP/HAZARD LAMPS



C268 (BLACK)

MULTIFUNCTION SWITCH

PIN	CIRCUIT	CIRCUIT FUNCTION
1	1039 (BK/YE)	Power (Hot in Run)
2	5 (OG/LB)	Right Rear Turn/Hazard Lamps
3	379 (BN/WH)	Right Cornering Lamp
4	383 (RD/WH)	Power (Hot at All Times)
5	2 (WH/LB)	Right Turn Indicator and Lamps
6	44 (LB)	Turn Signal Flasher Input
7	380 (VT/YE)	Left Cornering Lamps
8	3 (LG/WH)	Left Turn Indicator and Lamps
9	569 (DG)	Stop Lamp Input
10	9 (LG/OG)	Left Rear Turn/Hazard Lamps
11	385 (WH/RD)	Hazard Flasher Input



C2002 (BLACK)

BRAKE PEDAL POSITION (BPP) SWITCH

PIN	CIRCUIT	CIRCUIT FUNCTION
1	10 (LG/RD)	Power (Hot at All Times)
2	511 (LG)	Brake Applied Output



C269 (BLACK)

MULTIFUNCTION SWITCH

PIN	CIRCUIT	CIRCUIT FUNCTION
1	589 (OG)	Speed Select
2	932 (GY/WH)	Cornering Lamps
3	–	NOT USED
4	993 (BN/WH)	Ground
5	12 (LG/BK)	High Beam
6	590 (DB/WH)	Interval Delay Set
7	910 (PK)	Power (Hot at All Times)

CONNECTOR REFERENCE LIST

CONNECTOR	SECTION-PAGE
C162	42-3
C200	58-5
C220	58-4
C255	63-5