C199

12B637

A274
AX4S/AX4N Transmission



F10093

Pin	Circuit	Circuit Function
1	237 (OG/YE)	Shift solenoid A
2	361 (RD)	Voltage supplied in Start and Run (overload protected)
3	480 (VT/YE)	Torque Converter Clutch (TCC) solenoid
4	–	not used
5	923 (OG/BK)	Transmission Fluid Temperature (TFT) sensor, input
6	315 (VT/OG)	Shift solenoid B
7	361 (RD)	Voltage supplied in Start and Run (overload protected)
8	971 (PK/BK)	Shift solenoid C
9	359 (GY/RD)	signal, return
10	924 (BN/OG)	Powertrain Control Module (PCM), to Electronic Pressure Control (EPC) solenoid

C201a

14290

A112
Generic Electronic Module (GEM)



F12077

Pin	Circuit	Circuit Function
1	465 (WH/LB)	Low coolant level switch, input
2	547 (LG/YE)	Brake indicator, control
3	679 (GY/BK)	Vehicle Speed Sensor (VSS) +
4	385 (WH/RD)	Voltage supplied at all times (overload protected)
5	–	not used
6	938 (BK/LG)	Ground
7	–	not used
8	–	not used
9	–	not used
10	164 (VT/LB)	Daytime running lamps (DRL) relay, control
11	646 (YE/WH)	Wiper run/park relay, control
12	647 (GY/LB)	Wiper high/low relay, control