C294a (RD)

14401

Function selector switch assembly (19B888)



F04405

Pin	Circuit	Circuit function
1	181 (BN/OG)	Blower motor relay control
2	296 (WH/VT)	Voltage in Run (overload protected)
3	348 (VT)	A/C demand signal
4	295 (LB/PK)	Voltage in Run (overload protected)

C294b (BK)

14401

Function selector switch assembly (19B888)



F04193

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	261 (OG/BK)	Front blower motor (19805) – Low
3	754 (LG/WH)	Front blower motor (19805) – medium low
4	752 (YE/RD)	Front blower motor (19805) – medium high

C294c (BK)

14401

Function selector switch assembly (19B888)



F02243

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	19 (LB/RD)	Instrument illumination, feed

C294d (WH)

14401

Function selector switch assembly (19B888)



F03165

Pin	Circuit	Circuit function
1	438 (RD/WH)	Air temperature door variable resistor –
2	437 (YE/LG)	Air temperature door variable resistor, signal
3	436 (RD/LG)	Air temperature door variable resistor, +

C300 (BK)

14A504



F04140

(1) 566 (DG)
(2) 294 (WH/LB)
(3) 1153 (RD/BK)
(4) 57 (BK)

14B084



F04138

(1) 566 (DG)
(2) 294 (WH/LB)
(3) 1153 (RD/BK)
(4) 1057 (OG/BK)

C303 (YE)

14A504

Passenger safety belt retractor pretensioner



F02042

Pin	Circuit	Circuit function
1	1081 (YE/RD)	Passenger safety belt retractor pretensioner, feed
2	1082 (LB/BK)	Passenger safety belt retractor pretensioner, return