C202b (GY)

14A320

N442
Multifunction switch



F07051

Pin	Circuit	Circuit function
1	684 (PK/YE)	Wiper/washer, input
2	15 (RD/YE)	Power, Hot with Headlamps on
3	13 (RD/BK)	Power, Hot with Low Beams on
4	359 (GY/RD)	signal, return
	1302 (WH/LG)	Multifunction switch, Signal return
5	632 (GY/OG)	Power, Hot with High Beams on
6	680 (LB/OG)	Wiper/washer, delay input
7	196 (DB/OG)	Voltage supplied at all times (overload protected)

C205

14401

N113
Main light switch
(11654)



F11023

Pin	Circuit	Circuit function
1	–	not used
2	15 (RD/YE)	Power, Hot with Headlamps on
3	1032 (WH/BK)	Power, Exterior lamps
4	640 (RD/YE)	Voltage supplied in Start and Run (overload protected)
	192 (BN/WH)	Autolamp dimmer relay, output
5	195 (TN/WH)	Voltage supplied at all times (overload protected)
6	196 (DB/OG)	Voltage supplied at all times (overload protected)
7	57 (BK)	Ground
8	484 (OG/BK)	Headlamp switch, on input
9	235 (RD/BK)	Instrument illumination, input
10	–	not used
11	–	not used