C1017

14290

K22
Starter relay (11450)



F05051

Pin	Circuit	Circuit function
87	113 (YE/LB)	Starter motor (11002) to Starter relay (11450)
87A	–	not used
86	325 (DB/OG)	Starter relay (11450), control
85	1093 (TN/RD)	Power, Hot in Start with Park or Neutral
	33 (WH/PK)	
30	37 (YE)	Voltage supplied at all times (overload protected)

C1018

14290

V34
PCM power diode



F02009

Pin	Circuit	Circuit function
1	546 (DG/YE)	Voltage supplied in Start and Run (overload protected)
2	16 (RD/LG)	Voltage supplied in Start and Run (overload protected)
	16 (RD/LG)	Voltage supplied in Start and Run (overload protected)

C1021

14290

E1
Headlamp, left
(13008)



F03169

Pin	Circuit	Circuit function
1	12 (LG/BK)	Power, Hot with High Beams on
2	57 (BK)	Ground
3	1055 (WH/LG)	Headlamp, left (13008) - fused feed – Low beams

C1023

14290

E164
Park/turn lamp, left
front (13411)



F03099

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	14 (BN)	Power, Exterior lamps
3	3 (LG/WH)	Turn lamps, feed, left front

C1025

14290

N423
Deactivator switch



F02203

Pin	Circuit	Circuit function
1	276 (BN)	Voltage in Run (overload protected)
2	307 (BK/YE)	Brake pressure switch (2B264), input