C169

7E443

N19
Reversing lamps
switch



F02353

Pin	Circuit	Circuit function
1	140 (BK/PK)	Voltage supplied in reverse
2	1087 (OG)	Voltage in Run (overload protected)

C171 (GN)

12B637

B48
Heated Oxygen
Sensor (HO2S) #11
(9F472)



F04124

Pin	Circuit	Circuit function
1	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
2	387 (RD/WH)	Heated Oxygen Sensor (HO2S) #11 (9F472), heater
3	359 (GY/RD)	signal, return
4	74 (GY/LB)	Heated Oxygen Sensor (HO2S) #11 (9F472), input

C172 (GN)

12B637

B47
Heated Oxygen
Sensor (HO2S) #21
(9F472)



F04124

Pin	Circuit	Circuit function
1	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
2	388 (YE/LB)	Heated Oxygen Sensor (HO2S) #12 (9G444), heater
3	359 (GY/RD)	signal, return
4	94 (RD/BK)	Heated Oxygen Sensor (HO2S) #12 (9G444), input

C174

12B637

U10
Ignition transformer
capacitor 1 (18801)

F01031

Pin	Circuit	Circuit function
1	20 (WH/LB)	Voltage supplied in Start and Run (overload protected)