C139

Main Chassis Harness



3538635C1

Transmission Harness



3538634C1

(A) 140 (BK/PK)
(B) 325 (DB/OG) (Main Chassis Harness)
32 (RD/LB) (Manual Trans Harness)
325 (DB/OG) (LCT Trans Harness)
325 (DB/OG) (MD Trans Harness)
(C) 295 (LB/PK)
(D) 417 (VT/OG) (Manual Trans w/2-speed)
123 (RD) (LCT Trans Harness)
119 (PK/YE) (MD Trans Harness)(Cummins Engine)
PLUG (MD Trans Harness only)(CAT Engine)
(E) 125 (DB/WH) (LCT Trans Harness)
115 (LG/BK) (MD Trans Harness)
933 (BK/DG) (Manual Trans w/2-speed)
(F) 1290 (WH/OG)
PLUG (Manual Trans Harness only)
(G) 113 (YE/LB)
154 (VT/LG) (MD Trans Harness only)
PLUG (Manual Trans Harness only)
(H) 128 (VT/YE)
161 (DG/OG) (MD Trans Harness only)
PLUG (Manual Trans Harness only)
(J) 1064 (YE/LB)
107 (VT) (LCT Trans / CAT Engine only)
PLUG (Manual Trans Harness only)
(K) 1286 (RD/OG)
120 (PK/LG) (LCT Trans / CAT Engine only)
PLUG (Manual Trans Harness only)

C143

Dash Harness

A/C cycle switch



3576258C1

Pin	Circuit	Circuit Function
1	–	Not used
2	441 (RD/YE)	A/C head pressure switch to cyclic pressure switch
3	–	Not used
4	348 (VT)	Module, powertrain control to A/C demand signal

C145

Engine Harness (CAT & V8)



3574236C1

Dash Harness



3574235C1

(1) 569 (DG)
(2) 511 (LG) (V8 AVNT Engine)
21 (DG/LG) (CAT Engine)
(3) 32 (RD/LB) (CAT Engine)
329 (PK) (V8 AVNT Engine)
(4) 20 (WH/LB) (Dash Harness)
785 (BK/LG) (V8 AVNT Engine Harness)
PLUG (CAT Engine Harness)
(5) 814 (WH/BK)
PLUG (CAT Engine Harness only)
(6) 878 (PK/YE) (V8 AVNT Engine)
57 (BK) (CAT Engine)
(7)
(8) 643 (RD)
PLUG (CAT Engine Harness only)
(9) PLUG
(10) 238 (DG/YE)
(11) 327 (BK/OG)
PLUG (CAT Engine Harness only)
(12) 57 (BK)
(13) 361 (RD)
PLUG (V8 AVNT Engine Harness only)
(14) 361 (RD) (V8 AVNT Engine)
480 (VT/YE) (CAT Engine)
(15) 1065 (WH/LB)
PLUG (V8 AVNT Engine Harness only)
(16) 441 (RD/YE)