C228a

14401

A205
Electronic Automatic Temperature Control (EATC) module (19980)



F13013

Pin	Circuit	Circuit function
1	915 (PK/LB)	SCP Bus –
2	54 (LG/YE)	Voltage supplied at all times (overload protected)
3	57 (BK)	Ground
4	470 (PK/BK)	Sensor signal return (reference/ground)
5	–	not used
6	436 (RD/LG)	Air temperature door variable resistor +
7	767 (LB/OG)	Ambient air temperature sensor (19E702), feed
15	914 (TN/OG)	SCP Bus +
16	298 VT/OG	Voltage in Run (overload protected)
17	–	not used
18	437 (YE/LG)	Air temperature door variable resistor, wiper
19	19 (LB/RD)	Instrument illumination, feed
20	468 (BN)	Sunload sensor (19E663), input

C228b

14401

A205
Electronic Automatic Temperature Control (EATC) module (19980)



F13015

Pin	Circuit	Circuit function
8	1070 (BN/LB)	Audio/climate control switch
9	438 (RD/WH)	Air temperature door variable resistor –
10	569 (DG)	Brake pedal position switch (13480), to stoplamps
11	348 (VT)	A/C demand signal
12	–	not used
13	245 (BN/LG)	Blend door actuator, control
14	484 (OG/BK)	Lighting control module
21	790 (WH/OG)	In–vehicle temperature sensor (19C734), input
22	–	not used
23	752 (YE/RD)	Blower switch speed control, to resistor
24	754 (LG/WH)	Blower switch speed control, to resistor
25	506 (RD)	Switches, output
26	246 (VT)	Temperature blend door actuator (19E616), signal

C233

14401

B206
In–vehicle temperature sensor (19C734)



F02493

Pin	Circuit	Circuit function
1	790 (WH/OG)	In–vehicle temperature sensor (19C734), input
2	470 (PK/BK)	Sensor signal return (reference/ground)