C141 (BU/WH)

* Marauder

7C078

Heated Oxygen Sensor (HO2S) #22 (9G444)



F04369

Pin	Circuit	Circuit function
1	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
2	390 (TN/YE)	Heated Oxygen Sensor (HO2S) #22 (9G444), heater
3	359 (GY/RD)	signal return
4	393 (VT/LG)	Heated Oxygen Sensor (HO2S) #22 (9G444), input
	*393 (VT/LG)	Voltage supplied in Start and Run (overload protected)

C142 (BU/WH)

7C078

Heated Oxygen Sensor (HO2S) #12 (9G444)



F04369

Pin	Circuit	Circuit function
1	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
2	389 (WH/BK)	Heated Oxygen Sensor (HO2S) #12 (9G444), heater
3	359 (GY/RD)	signal, return
4	392 (RD/LG)	Heated Oxygen Sensor (HO2S) #12 (9G444), input

C144

12A654



F02085

12B637



F02373

(1) 359 (GY/RD)
(2) 1102 (YE/LG)

C145 (GY/BK)

* Natural Gas Vehicle (NGV)

14290



F16034

14401



F16141

(1) 914 (TN/OG)
(2) 617 (PK/OG)
(3) 618 (VT/LG)
(4) 160 (DB/WH)
(5) 915 (PK/LB)
(6) 70 (LB/WH)
(7) 249 (DB/LG)
(8) 688 (GY/LB)
(9) 1907 (WH/LG)
(10) 12 (LG/BK)
(11) 3062 (BK/WH)
*875 (BK/LB)
(12) 961 (WH/PK)
(13) 379 (BN/WH)
(14) 2 (WH/LB)
(15) 532 (OG/YE)
(16) 161 (DG/OG)