C1058 (BK)

14290

Low speed fan control relay



F05129

Pin	Circuit	Circuit function
30	538 (GY/RD)	Low speed fan control relay, switched power – ZETEC
	229 (RD/OG)	Low speed fan control relay, output – Duratec
85	296 (WH/VT)	Voltage supplied in Start and Run (overload protected)
86	386 (LB)	Low speed fan control relay, control – ZETEC
	228 (DB)	Low speed fan control relay, control – Duratec
87	60 (BK/LG)	Voltage supplied at all times (overload protected) – ZETEC
	30 (BK/LG)	Voltage supplied at all times (overload protected) – Duratec
87A	–	not used

C1062 (BK)

14290

Dual pressure switch (19D594)



F04255

Pin	Circuit	Circuit function
1	198 (DG/OG)	Dual pressure switch (19D594), signal
2	347 (BK/YE)	Dual pressure switch (19D594), signal
3	571 (BK/OG)	Ground
4	441 (RD/YE)	A/C pressure switch, to A/C cycling switch

C1064 (GY)

9H589

Engine Coolant Temperature (ECT) sensor (12A648)



F02091

Pin	Circuit	Circuit function
1	354 (LG/RD)	Engine Coolant Temperature (ECT) sensor (12A648), input
2	89 (OG)	signal, return

C1065 (BK)

12A522

Ignition coil (12029)



F03203

Pin	Circuit	Circuit function
1	1030 (DG/VT)	Ignition coil (12029), control
2	296 (WH/VT)	PCM power relay, output
3	1024 (LG/WH)	Ignition coil (12029), control

C1066 (BK)

9H589

Idle air control valve (IAC) (9F715)



F02091

Pin	Circuit	Circuit function
1	100 (WH/RD)	PCM power relay, output
2	264 (WH/LB)	Idle air control valve (IAC) (9F715), control