C193

7C078

B110
Output Shaft Speed
(OSS) sensor
(7M101)



F02069

Pin	Circuit	Circuit function
1	359 (GY/RD)	signal, return
2	970 (DG/WH)	Output Shaft Speed (OSS) sensor (7M101)

C194

12B637

U11
Ignition transformer
capacitor 2 (18801)

F01031

Pin	Circuit	Circuit function
1	1118 (RD)	PCM power relay, output

C197a

14B060

M8
Starter motor
(11002)



F01061

Pin	Circuit	Circuit function
1	33 (WH/PK)	Starter relay (11450), output

C197b

14B060

M8
Starter motor
(11002)



F01115

Pin	Circuit	Circuit function
1	2037 (RD)	Battery cable +

C199

7C078

A40
Transmission hard-
ware unit



F10093

Pin	Circuit	Circuit function
1	–	not used
2	359 (GY/RD)	signal, return
3	924 (BN/OG)	Torque Converter Clutch (TCC) solenoid
4	361 (RD)	Voltage supplied in Start and Run (overload protected)
5	923 (OG/BK)	Transmission Fluid Temperature (TFT) sensor, input
6	925 (WH/YE)	Electronic Pressure Control (EPC) solenoid, control
7	237 (OG/YE)	Shift solenoid A
8	315 (VT/OG)	Shift solenoid B
9	–	not used
10	–	not used