C1221 (GY/BK)

* with manual A/C

12B637



F16067

(1) 262 (BN/PK)
(2) 126 (VT/YE)
(3) 390 (TN/YE)
(4) 237 (OG/YE)
(5) 925 (WH/YE)
(6) 388 (YE/LB)
(7) 94 (RD/BK)
(8) 389 (WH/BK)
(9) 392 (RD/LG)
(10) 393 (VT/LG)
(11) *361 (RD)
(12) 199 (LB/YE)
(13) 136 (DB/YE)
(14) 315 (VT/OG)
(15) 923 (OG/BK)
(16) 359 (GY/RD)

7C078



F16141

(1) 262 (BN/PK)
(2) 126 (VT/YE)
(3) 390 (TN/YE)
(4) 237 (OG/YE)
(5) 925 (WH/YE)
(6) 388 (YE/LB)
(7) 94 (RD/BK)
(8) 389 (WH/BK)
(9) 392 (RD/LG)
(10) 393 (VT/LG)
(11) 361 (RD)
(12) 199 (LB/YE)
(13) 136 (DB/YE)
(14) 315 (VT/OG)
(15) 923 (OG/BK)
(16) 359 (GY/RD)

C1227 (BK)

14290

Front blower motor (19805)



F02329

Pin	Circuit	Circuit function
1	371 (PK/WH)	Blower motor relay, switched power, output
2	515 (OG/RD)	blower motor, speed control
	261 (OG/BK)	Front blower motor (19805) to switch, Resistor

C1257

12B637

Fuel rail temperature sensor



F02545

Pin	Circuit	Circuit function
1	791 (RD/PK)	Fuel rail temperature sensor, signal
2	359 (GY/RD)	signal, return

C1258

12B637

Fuel rail cutoff valve



F04263

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	–	not used
3	787 (PK/BK)	Natural Gas Vehicle (NGV) tank, Power
4	–	not used