C294a

14401

P82
Function selector
switch assembly,
front



F04027

Pin	Circuit	Circuit function
1	489 (PK/BK)	Voltage, hot in run only
2	753 (YE/RD)	Center console, Heater blower motor (19805), feed
3	348 (VT)	A/C demand signal
4	489 (PK/BK)	Voltage, hot in run only

C294b

14401

P82
Function selector
switch assembly,
front



F04193

Pin	Circuit	Circuit function
1	261 (OG/BK)	Blower motor, to switch – High
2	57 (BK)	Ground
3	260 (RD/OG)	Blower motor relay, control
4	269 (LB/OG)	Heater blower motor (19805), to, Heater blower switch

C294c

14401

P82
Function selector
switch assembly,
front



F06277

Pin	Circuit	Circuit function
1	752 (YE/RD)	Blower switch speed control, to resistor
2	757 (RD/WH)	Auxiliary blower motor resistor assembly (19A706), to, Auxiliary blower motor (19805)
3	–	not used
4	57 (BK)	Ground
5	751 (DB/WH)	Auxiliary blower motor resistor assembly (19A706), output
6	754 (LG/WH)	Blower switch speed control, to resistor

C294d

14401

P82
Function selector
switch assembly,
front



F03165

Pin	Circuit	Circuit function
1	438 (RD/WH)	Air temperature door variable resistor –
2	437 (YE/LG)	Air temperature door variable resistor, wiper
3	436 (RD/LG)	Air temperature door variable resistor +