C168 (GY)

15525

4R70W transmission



F10076

Pin	Circuit	Circuit function
1	–	not used
2	359 (GY/RD)	Signal return
3	480 (VT/YE)	Torque Converter Clutch (TCC) solenoid, control
4	1138 (VT/WH)	Voltage supplied in Start and Run (overload protected)
5	923 (OG/BK)	Transmission Fluid Temperature (TFT) sensor, signal
6	925 (WH/YE)	Electronic Pressure Control (EPC) solenoid, control
7	237 (OG/YE)	Shift solenoid A, control
8	315 (VT/OG)	Shift solenoid B, control
9	–	not used
10	–	not used

C169 (NA)

15525

Reversing lamps switch



F02471

Pin	Circuit	Circuit function
1	140 (BK/PK)	Voltage supplied in reverse, output
2	295 (LB/PK)	Voltage in Run (overload protected)

C171 (GY)

12B637/15525/9D930

Heated Oxygen Sensor (HO2S) #11 (9F472)



F04075

Pin	Circuit	Circuit function
1	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
2	387 (RD/WH)	Heated Oxygen Sensor (HO2S) #11 (9F472), heater, control
3	359 (GY/RD)	signal, return
4	74 (GY/LB)	Sensor signal