Pin	Circuit	Circuit Function
41	439 (TN/LG)	A/C pressure switch, signal
42	1101 (GY/RD)	Injector 10 (9F593), control
43	–	not used
44	–	not used
45	39 (RD/WH)	Engine Coolant Temperature (ECT) sender, input
46	679 (GY/BK)	Vehicle Speed Sensor (VSS) +
47	–	not used
48	648 (WH/PK)	Tachometer, signal
49	1145 (LB/BK)	Digital Transmission Range (DTR) sensor, TR2
50	1143 (WH/BK)	Digital Transmission Range (DTR) sensor, TR4
51	570 (BK/WH)	Ground
52	1028 (WH/PK)	Coil On Plug (COP) 5 (12029), control
53	1030 (DG/VT)	Coil On Plug (COP) 7 (12029), control
54	480 (VT/YE)	Torque Converter Clutch (TCC) solenoid
55	785 (BK/LG)	Voltage supplied at all times (overload protected)
56	191 (LG/BK)	Powertrain Control Module (PCM) (12A650), to, EVAP canister purge valve
57	310 (YE/RD)	Knock sensor (12A699)
58	–	not used
59	970 (DG/WH)	Turbine shaft speed sensor (7M101)
60	74 (GY/LB)	Heated Oxygen Sensor (HO2S) #11 (9G444), input
61	–	not used
62	–	not used
63	–	not used
64	199 (LB/YE)	Digital Transmission Range (DTR) sensor, TR3A
65	–	not used

Pin	Circuit	Circuit Function
66	1102 (YE/LG)	Cylinder–head temperature sensor (6G004), to, Powertrain Control Module (PCM) (12A650)
67	–	not used
68	1100 (GY/BK)	Injector 9 (9F593), control
69	331 (PK/YE)	A/C clutch relay, control
70	–	not used
71	361 (RD)	Voltage supplied in Start and Run (overload protected)
72	561 (TN/RD)	Injector 7, control
73	559 (TN/BK)	Injector 5, control
74	557 (BN/YE)	Injector 3, control
75	555 (TN)	Injector 1, control
76	570 (BK/WH)	Ground
77	570 (BK/WH)	Ground
78	1027 (PK/LB)	Coil On Plug (COP) 2 (12029), control
79	1029 (WH/RD)	Coil On Plug (COP) 8 (12029), control
80	926 (LB/OG)	Fuel pump relay, control
81	925 (WH/YE)	Electronic Pressure Control (EPC) solenoid, control
82	1142 (WH/RD)	Coil On Plug (COP) 9, control
83	264 (WH/LB)	Idle air control valve (IAC) (9F715), control
84	136 (DB/YE)	Powertrain Control Module (PCM) (12A650), – Output Shaft Speed (OSS) sensor (7M101)
85	795 (DG)	Camshaft position sensor (6B288), to, Powertrain Control Module (PCM) (12A650)
86	–	not used
87	94 (RD/BK)	Heated Oxygen Sensor (HO2S) #21 (9G444), input
88	967 (LB/RD)	Mass Air Flow (MAF) sensor (12B579), output
89	355 (GY/WH)	Throttle Position Sensor (TPS) (9B989), input
90	351 (BN/WH)	Reference, voltage
91	359 (GY/RD)	signal, return
92	810 (RD/LG)	Brake pedal position switch (13480), output