C270f (BK)

14A005

Central Junction
Box (CJB) (14A068)



F07083

Pin	Circuit	Circuit function
1	1542 (RD)	Voltage supplied at all times (overload protected)
2	1389 (WH)	Rear window defrost relay, control
3	1332 (LB)	Accessory delay relay, control
4	956 (OG/LG)	Voltage supplied at all times (overload protected)
5	400 (LB/BK)	Accessory relay, switched power, output
6	186 (BN/LB)	Rear window defrost relay, switched power
7	536 (BK/LG)	Auxiliary blower motor (19805), relay control battery feed

C270g (BU)

14A005

Central Junction
Box (CJB) (14A068)



F08167

Pin	Circuit	Circuit function
1	1455 (GY/RD)	Fused battery feed, SSP 3 relay, output
2	1330 (YE/LB)	SSP 3 relay, SSP 4 relay, control
3	1458 (VT/WH)	Fused battery feed, SSP 3 relay, output, to, courtesy lamps
4	1456 (RD/LB)	Fused battery feed, SSP 3 relay, to, High mounted stop lamp
5	400 (LB/BK)	Accessory relay, switched power, output
6	1457 (RD/YE)	Fused battery feed, SSP 4 relay, output
7	194 (PK)	Accessory delay, relay control battery feed
8	1454 (TN/RD)	Fused battery feed, SSP 4 relay, to, Rear Electronic Module (REM)

C271 (BK)

14401

Front blower motor
speed controller
(19E624)



F04247

Pin	Circuit	Circuit function
1	1205 (BK)	Ground, blower motor, High
2	261 (OG/BK)	Blower motor, speed control
3	269 (LB/OG)	medium low
4	260 (RD/OG)	medium high