* supercharged

C1051

12A581

K4
Fuel pump relay



F05051

Pin	Circuit	Circuit function
30	1059 (LB/OG)	Voltage supplied at all times (overload protected)
85	926 (LB/OG)	Fuel pump relay, control
86	361 (RD)	Voltage supplied in Start and Run (overload protected)
87	238 (DG/YE)	Fuel pump relay, switched output
	*866 (WH)	Fuel pump relay, switched output
87a	–	not used

C1066

12B637/9D930

Y133
Idle Air Control
(IAC) valve (9F715)



F02111

Pin	Circuit	Circuit function
1	361 (RD)	Voltage supplied in Start and Run (overload protected)
2	264 (WH/LB)	Idle Air Control (IAC) valve (9F715), control

C1072

12B637/9D930

Y205
EGR vacuum regu-
lator solenoid
(9J459)



F02101

Pin	Circuit	Circuit function
1	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
2	360 (BN/PK)	EGR Vacuum Regulator (EVR), control

C1078

12A581

N126
A/C high pressure
switch (19D594)



F04195

Pin	Circuit	Circuit function
1	441 (RD/YE)	A/C high pressure switch (19D594), to A/C cycling switch
2	–	not used
3	348 (VT)	A/C demand signal
4	–	not used

C1086

12A581

V7
A/C Compressor
clutch diode



F02009

Pin	Circuit	Circuit function
1	321 (GY/WH)	A/C clutch relay, switched output
2	57 (BK)	Ground