C1029

14290

Y134
EVAP canister purge valve



F02105

Pin	Circuit	Circuit function
1	361 (RD)	Voltage supplied in Start and Run (overload protected)
2	191 (LG/BK)	Powertrain Control Module (PCM) (12A650), EVAP canister purge valve

C1030

14290

A253
Daytime Running Lamps (DRL) module



F06110

Pin	Circuit	Circuit function
1	13 (RD/BK)	Power, Hot with Low Beams on
2	54 (LG/YE)	Voltage supplied at all times (overload protected)
3	298 (VT/OG)	Voltage in Run (overload protected)
4	57 (BK)	Ground
5	12 (LG/BK)	Power, Hot with High Beams on
6	–	not used

C1031

14290

M3
Heater blower motor (19805)



F02169

Pin	Circuit	Circuit function
1	261 (OG/BK)	Blower motor, to switch - High
2	371 (PK/WH)	Blower motor relay, switched output

C1032

14290

R77
Heater blower motor resistor, front (19A706)



F04674

Pin	Circuit	Circuit function
1	754 (LG/WH)	Blower switch speed control, to resistor
2	57 (BK)	Ground
3	752 (YE/RD)	Blower switch speed control, to resistor
4	261 (OG/BK)	Blower motor, to switch - High

C1035

14A280

P93
Battery Junction Box (BJB) (14A003)



F02357

Pin	Circuit	Circuit function
1	2037 (RD)	Battery cable +
	2037 (RD)	Battery cable +