C290c (BK)

14401

Radio (18806)



F20071

Pin	Circuit	Circuit function
1	–	not used
2	–	not used
3	–	not used
4	–	not used
5	1068 (LG/BK)	Audio System ON (ASYSON)
6	832 (LB/PK)	Audio corporate protocol A
7	833 (TN)	Audio corporate protocol B
8	–	not used
9	–	not used
10	–	not used
11	–	not used
12	–	not used
13	–	not used
14	–	not used
15	–	not used
16	–	not used
17	–	not used
18	–	not used
19	–	not used
20	–	not used

C294a (RD)

14401

Function selector switch assembly, front



F04405

Pin	Circuit	Circuit function
1	1003 (GY/YE)	Voltage in Run (overload protected)
2	348 (VT)	A/C demand signal
3	260 (RD/OG)	Blower motor relay, control
4	364 (BK/LG)	Voltage in Run (overload protected)

* XLS

C294b (BK)

14401

Function selector switch assembly, front



F02243

Pin	Circuit	Circuit function
1	235 (RD/BK)	Instrument illumination +
	*19 (LB/RD)	Instrument illumination +
2	57 (BK)	Ground

C294c (BK)

14401

Function selector switch assembly, front



F04193

Pin	Circuit	Circuit function
1	261 (OG/BK)	Blower motor, to switch - High
2	754 (LG/WH)	Blower switch speed control, to resistor
3	57 (BK)	Ground
4	752 (YE/RD)	Blower switch speed control, to resistor