C1030

14290

A253
Daytime Running Lamps (DRL) module



F06110

Pin	Circuit	Circuit function
1	13 (RD/BK)	Power, Hot with Low Beams on
2	196 (DB/OG)	Voltage supplied at all times (overload protected)
3	298 (VT/OG)	Voltage in Run (overload protected)
4	57 (BK)	Ground
5	12 (LG/BK)	Power, Hot with High Beams on
6	–	not used

C1033

* Natural Gas Vehicle (NGV)

12A581



F16091

(1) 1025 (OG/YE)
(2) 1021 (LG/YE)
(3) 1030 (DG/VT)
(4) 1029 (WH/RD)
(5) 883 (PK/LB)
*298 (VT/OG)
(6) 295 (LB/PK)
*676 (PK/OG)
(7) 321 (GY/WH)
*39 (RD/WH)
(8) 191 (LG/BK)
*321 (GY/WH)
(9) *388 (YE/LB)
(10) 57 (BK)
(11) 388 (YE/LB)
(12) 36 (YE/WH)
*883 (PK/LB)
(13) 74 (GY/LB)
(14) 94 (RD/BK)
(15) 387 (RD/WH)
(16) 32 (RD/LB)

12B637



F16020

(1) 1025 (OG/YE)
(2) 1021 (LG/YE)
(3) 1030 (DG/VT)
(4) 1029 (WH/RD)
(5) 883 (PK/LB)
*295 (LB/PK)
(6) 295 (LB/PK)
*676 (PK/OG)
(7) 321 (GY/WH)
*39 (RD/WH)
(8) 191 (LG/BK)
*321 (GY/WH)
(9) *388 (YE/LB)
(10) 57 (BK)
(11) 388 (YE/LB)
(12) 36 (YE/WH)
*883 (PK/LB)
(13) 74 (GY/LB)
(14) 94 (RD/BK)
(15) 387 (RD/WH)
(16) 32 (RD/LB)