C193

12B637

B110
Output Shaft Speed
(OSS) sensor
(7M101)



F02373

Pin	Circuit	Circuit function
1	136 (DB/YE)	Powertrain Control Module (PCM) (12A650) – Output Shaft Speed (OSS) sensor (7M101)
2	359 (GY/RD)	signal, return

C197a

12B637

M8
Starter motor
(11002)



F01085

Pin	Circuit	Circuit function
1	113 (YE/LB)	Starter motor (11002), to, Starter relay (11450)

C197b

14B060

M8
Starter motor
(11002)



F01085

Pin	Circuit	Circuit function
1	2037 (RD)	Starter relay (11450), output

C199

12B637

A274
AX4S/4F50N Trans-
mission



F10076

Pin	Circuit	Circuit function
1	–	not used
2	473 (RD/LB)	Torque Converter Clutch (TCC) solenoid
3	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
4	237 (OG/YE)	Shift solenoid A
5	971 (PK/BK)	Shift solenoid C
6	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
7	315 (VT/OG)	Shift solenoid B
8	923 (OG/BK)	Transmission Fluid Temperature (TFT) sensor, input
9	925 (WH/YE)	Electronic Pressure Control (EPC) solenoid, control
10	359 (GY/RD)	signal, return