C1030 (GY)

14290

Daytime Running Lamps (DRL) module



F06110

Pin	Circuit	Circuit function
1	13 (RD/BK)	Power, Hot with Low Beams on
2	54 (LG/YE)	Voltage supplied at all times (overload protected)
3	298 (VT/OG)	Voltage in Run (overload protected)
4	57 (BK)	Ground
5	12 (LG/BK)	Power, Hot with High Beams on
6	–	not used

C1031 (BK)

14290

Heater blower motor (19805)



F02169

Pin	Circuit	Circuit function
1	261 (OG/BK)	Blower motor, to switch - High
2	371 (PK/WH)	Blower motor relay, switched output

C1032 (BK)

14290

Heater blower motor resistor, front (19A706)



F04674

Pin	Circuit	Circuit function
1	754 (LG/WH)	Blower switch speed control, to resistor
2	57 (BK)	Ground
3	752 (YE/RD)	Blower switch speed control, to resistor
4	261 (OG/BK)	Blower motor, to switch - High

C1035

14A280

Battery Junction Box (BJB) (14A003)



F02357

Pin	Circuit	Circuit function
1	2037 (RD)	Battery cable +
	2037 (RD)	Battery cable +

C1038

14290

Fog lamp isolation relay



F05064

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	12 (LG/BK)	Power, Hot with High Beams on
3	14 (BN)	Power, Exterior lamps
4	474 (OG/LG)	Fog lamp relay, control
5	–	not used