C3028 (BK)

14405

CD changer
(18D806)



F12103

Pin	Circuit	Circuit function
1	832 (LB/PK)	Audio corporate protocol A
2	–	not used
3	694 (BK/LG)	Ground
4	–	not used
5	856 (VT)	Radio (18806), to CD changer, Left +
6	690 (GY)	Radio (18806), to CD changer, Right +
7	833 (TN)	Audio corporate protocol B
8	1068 (LG/BK)	Audio System ON (ASYSON)
9	828 (VT/LB)	Voltage supplied at all times (overload protected)
10	48	Shield
11	798 (LG/RD)	Radio (18806), to CD changer, Left –
12	799 (OG/BK)	Radio (18806), to CD changer, Right –

C3043 (BK/GY)

14A699

Occupant classification sensor module



F10137

Pin	Circuit	Circuit function
A	–	not used
B	–	not used
C	–	not used
D	676 (PK/OG)	Ground
E	1557 (DB/OG)	Restraints control module (14B321), signal
F	1556 (DG/VT)	Restraints control module (14B321), signal
G	964 (DB/LG)	Voltage supplied in Start and Run (overload protected)
H	1569 (GY/LB)	Seat pressure sensor, Signal return
J	1568 (RD/WH)	Occupant classification sensor module, switched power
K	1570 (TN/BK)	Occupant classification sensor module, signal

C3042 (BK)

14A699

Seat pressure sensor

F03285

Pin	Circuit	Circuit function
A	1569 (GY/LB)	Occupant classification sensor module, Signal return
B	1570 (TN/BK)	Seat pressure sensor, signal
C	1568 (RD/WH)	Occupant classification sensor module, switched power

C3047 (GY)

14A005



F04367

14A699



F04148

(1) –
(2) 1257 (WH/LB)
(3) 1258 (RD)
(4) –