C289

19D570/19D887

M256
Temperature blend
door actuator
(19E616)



F08015

Pin	Circuit	Circuit function
1	437 (YE/LG)	with Electronic Automatic Temperature Control (EATC), Air temperature door variable resistor, wiper
	351 (BN/WH)	manual A/C, Reference, – not used
2	–	with Electronic Automatic Temperature Control (EATC), not used
	–	manual A/C, not used
3	–	with Electronic Automatic Temperature Control (EATC), not used
	437 (YE/LG)	manual A/C, Air temperature door variable resistor, wiper, command
4	–	with Electronic Automatic Temperature Control (EATC), not used
	438 (RD/WH)	manual A/C, Air temperature door variable resistor -
5	438 (RD/WH)	with Electronic Automatic Temperature Control (EATC), Air temperature door variable resistor -
	–	manual A/C, not used
6	436 (RD/LG)	with Electronic Automatic Temperature Control (EATC), Air temperature door variable resistor +
	436 (RD/LG)	manual A/C, Air temperature door variable resistor +
7	249 (DB/LG)	with Electronic Automatic Temperature Control (EATC), Blend door actuator, motor drive, CW
	1087 (OG)	manual A/C, Voltage in Run (overload protected)
8	250 (OG)	with Electronic Automatic Temperature Control (EATC), Blend door actuator, motor drive CCW
	57 (BK)	manual A/C, Ground

C291

14401



F02034

14A411



F02056