## C2168

**14401**

D54
Program remote keyless entry module connector



F02090

| Pin | Circuit | Circuit function |
|---|---|---|
| 1 | 57 (BK) | Ground |
| 2 | 25 (DB/OG) | Anti–theft |

## C2169

**14401**

P29
Non–Daytime running lamps jumper




F08050

| Pin | Circuit | Circuit function |
|---|---|---|
| 1 | – | not used |
| 2 | 15 (RD/YE) | Power, Hot with Headlamps on |
| 3 | 57 (BK) | Ground |
| 4 | 13 (RD/BK) | Power, Hot with Low Beams on |
| 5 | 471 (OG/LG) | Daytime running lamps resistor, to, Headlamp relay |
| 6 | 295 (LB/PK) | Voltage in Run (overload protected) |
| 7 | 1033 (RD/YE) | Daytime Running Lamps (DRL) relay, Relay, switched power |
| 8 | – | not used |

## C2171

**14401**

B8
Throttle Position Sensor (TPS) (9B989)




F04269

| Pin | Circuit | Circuit function |
|---|---|---|
| 1 | 21 (DK/LG) | Powertrain Control Module (PCM) (12A650) – Flexible fuel sensor |
| 2 | 216 (TN/RD) | Throttle Position Sensor (TPS) (9B989), input |
| 3 | – | not used |
| 4 | 359 (GY/RD) | signal, return |

## C2172

**14401**

N616
Idle validation switch



F02072

| Pin | Circuit | Circuit function |
|---|---|---|
| 1 | 1285 (RD/LG) | Idle validation switch, control |
| 2 | 1140 (VT) | PCM power relay, Switched, Power (Start or Run) |