C443

18W862

K1
Rear window defrost relay



F05062

Pin	Circuit	Circuit Function
30	186 (BN/LB)	Rear window defrost relay, switched power
86	1050 (LG/VT)	Voltage in Run (overload protected)
85	688 (GY/LB)	Rear window defrost relay, control
87	185 (BK)	Voltage supplied at all times (overload protected)
87A	–	not used

C447

12614

Y286
Shock actuator, left rear



F04251

Pin	Circuit	Circuit Function
1	57 (BK)	Ground
2	–	not used
3	842 (WH/OG)	Shock actuator, left rear
4	–	not used

C448

18W862

Y287
Shock actuator, right rear



F04075

Pin	Circuit	Circuit Function
1	57 (BK)	Ground
2	–	not used
3	843 (WH)	Shock actuator, right rear
4	–	not used

C450

18W862

Y131
Evaporative emission (EVAP) canister vent valve (9F945)



F02101

Pin	Circuit	Circuit Function
1	276 (BN)	Voltage supplied in Start and Run (overload protected)
2	91 (VT/WH)	Evaporative emission (EVAP) canister vent valve (9F945)

C451

13412

E105
Reversing lamp, left (13411)



F02223

Pin	Circuit	Circuit Function
1	57 (BK)	Ground
2	140 (BK/PK)	Voltage supplied in reverse

C461

13412

E109
Reversing lamp, right (13411)



F02223

Pin	Circuit	Circuit Function
1	57 (BK)	Ground
2	140 (BK/PK)	Voltage supplied in reverse