C1255

14290

ABS relay



F05110

Pin	Circuit	Circuit function
1	960 (BK/LB)	ABS relay, control
2	88 (BK/WH)	Voltage supplied in Start and Run (overload protected)
3	88 (BK/WH)	Voltage supplied in Start and Run (overload protected)
4	–	not used
5	939 (VT)	ABS relay, switched output

C1274

7C078

4R70W trans-
mission



F10093

Pin	Circuit	Circuit function
1	–	not used
2	359 (GY/RD)	signal, return
3	126 (VT/YE)	Torque Converter Clutch (TCC) solenoid
4	391 (RD/YE)	Voltage supplied in Start and Run (overload protected)
5	923 (OG/BK)	Transmission Fluid Temperature (TFT) sensor, input
6	925 (WH/YE)	Electronic Pressure Control (EPC) solenoid
7	237 (OG/YE)	Shift solenoid A
8	315 (VT/OG)	Shift solenoid B
9	–	not used
10	–	not used

C1260 (BK)

12B637

A/C pressure
transducer
sensor



F04195

Pin	Circuit	Circuit function
1	351 (BN/WH)	Reference, voltage
2	359 (GY/RD)	signal, return
3	–	not used
4	1154 (WH/BK)	A/C pressure transducer sensor