C250 (BK)

14401

Ignition switch
(11572)



F15009

Pin	Circuit	Circuit function
I2	–	not used
B1	37 (YE)	Voltage supplied at all times (overload protected)
A1	297 (BK/LG)	Voltage in Run or Accessory (overload protected)
P1	512 (TN/LG)	Brake indicator, control
GND	57 (BK)	Ground
P2	–	not used
B2	37 (YE)	Voltage supplied at all times (overload protected)
A2	–	not used
STA	32 (RD/LB)	Voltage supplied in Start (overload protected)
B3	–	not used
A3	–	not used
B5	37 (YE)	Voltage supplied at all times (overload protected)
I1	1050 (LG/VT)	Voltage supplied at all times (overload protected)
A4	687 (GY/YE)	Voltage in Run (overload protected)
B4	37 (YE)	Voltage supplied at all times (overload protected)

C251 (BK)

14401

Data Link Connector
(DLC) (14489)



F16063

Pin	Circuit	Circuit function
1	–	not used
2	914 (TN/OG)	SCP Bus +
3	–	not used
4	57 (BK)	Ground
5	570 (BK/WH)	Ground
6	–	not used
7	70 (LB/WH)	ISO Bus
8	–	not used
9	–	not used
10	915 (PK/LB)	SCP Bus –
11	–	not used
12	–	not used
13	107 (VT)	Module programming signal
14	–	not used
15	–	not used
16	693 (OG)	Voltage supplied at all times (overload protected)