C196 (BK)

14290

Daytime running lamps resistor



F04082

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	–	not used
3	–	not used
4	932 (GY/WH)	Daytime Running Lamps (DRL) relay, switched output

C197a

14B060

Starter motor (11002)



F01195

Pin	Circuit	Circuit function
1	605 (RD)	Voltage supplied at all times (not overload protected)

C197b

12B637

Starter motor (11002)



F01187

Pin	Circuit	Circuit function
1	33 (WH/PK)	switched power, to starter solenoid

C198 (BK)

14290

Ambient air temperature sensor (19E702)



F02617

Pin	Circuit	Circuit function
1	470 (PK/BK)	Sensor signal return (reference/ground)
2	788 (RD/OG)	Ambient air temperature sensor (19E702), input

C199 (WH)

12B637

AX4S/4F50N Transmission



F10093

Pin	Circuit	Circuit function
1	–	not used
2	480 (VT/YE)	Torque Converter Clutch (TCC) solenoid
3	361 (RD)	Voltage supplied in Start and Run (overload protected)
4	237 (OG/YE)	Shift solenoid A
5	971 (PK/BK)	Shift solenoid C
6	361 (RD)	Voltage supplied in Start and Run (overload protected)
7	315 (VT/OG)	Shift solenoid B
8	923 (OG/BK)	Transmission Fluid Temperature (TFT) sensor, input
9	924 (BN/OG)	Electronic Pressure Control (EPC) solenoid
10	359 (GY/RD)	signal, return